

QUICK Bengalack Avfetting Spray

Product description

Type

QUICK Bengalack Avfetting Spray is a special cleaner for greasy surfaces.

Features and benefits

Effectively removes grease and oil. Vapors away quickly. Does not damage painted surfaces, glass or plastic.

Recommended use

QUICK Bengalack Avfetting Spray is used for degreasing metal, eg. steel and aluminum. Can also be used for cleaning tools and engines, as well as cleaning of brakes, skis, bicycle chains and car wheel rims. The product can also be used for removing residues of stickers, glue and stearin.

Product data

Packaging size	Spray can (net content about 400 ml).
Flash point	Closed cup: -7°C (19.4°F)

Application data

Remarks

Propellant: Butane/propane.

The product is classified as extremely flammable.

On sensitive surfaces, it is recommended to do a test in an inconspicuous place to check if the surface can withstand **QUICK Bengalack Avfetting Spray**.

Application equipment / methods

Shake well before use.

Apply plenty. Leave on for 15–30 seconds. Wipe off using a lint free cloth. Repeat if necessary.

Drying times

The drying time is affected by temperature, air humidity and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Recoatable, minimum	Ca 20–30 minutes.
----------------------------	-------------------

Storage

Can be stored in freezing temperatures.

Disposal of waste

Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

55805237

NOBB module number

42168614

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway

Tel: +47 32 24 43 00
Fax: +47 32 84 13 85
SDSscanox@scanox.no

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.